KSM Series Side Actuated Detect Switches





Features/Benefits

- Low profile 1,5 mm
- Momentary, normally closed contact
- Gold contacts
- RoHS compliant and compatible

Typical Applications

- Automotive
- Position sensing switch
- Edge card reset switch
- Smart card presence switch detector
- DSL and fiber optic networks

Specifications

FUNCTION: Momentary action
CONTACT TYPE: SPST Normally closed

Mechanical

TOTAL TRAVEL:

TRAVEL TO BREAK: KSM1131D LFG 0.35 ± 0.15 mm

KSM6161 LFG 0,5 \pm 0,20 mm KSM1131D LFG 1,25 \pm 0,2 mm

KSM6161 LFG $1,92 \pm 0,2 \text{ mm}$

SWITCHING FORCE:

KSM1131D LFG $0,15N \le Fce \le 0,90 \text{ N}$ KSM6161 LFG $0,50N \le Fce \le 0,90 \text{ N}$

OPERATING LIFE: KSM1131D LFG 50,000 cycles

KSM6161 LFG 200,000 cycles

Packaging

Switches are delivered on continuous tape, in reels of 2,000 pieces (KSM1131D LFG) and 1250 pieces (KSM6161 LFG)

Electrical KSM1131D LFG **KSM6161 LFG** MAXIMUM POWER: 0.2 VA 1.0 VA MAXIMUM VOLTAGE: 24 VDC 32 VDC MINIMUM VOLTAGE: 20 mV 20 mV MAXIMUM CURRENT DC: 50 mA 50 mA MINIMUM CURRENT DC: 1 mA \leq 300 m Ω \leq 900 m Ω CONTACT RESISTANCE: INSULATION RESISTANCE: $\geq 10^9 \, \Omega$ $\geq 10^9$ ≥ 250 Vrms DIELECTRIC STRENGTH: ≥ 250 Vrms **BOUNCE TIME:** ≤ 10 ms \leq 1,25 ms

Environmental

OPERATING TEMPERATURE: -40°C to +85°C STORAGE TEMPERATURE: -55°C to +85°C

Process

SOLDERING: Compatible with lead free reflow process


NOTE: Specifications listed above are for switches with standard options. For information on specific and custom switches, consult Customer Service Center.

How To Order

Our easy build-a-switch concept allows you to mix and match options to create the switch you need. To order, select desired option from each category and place it in the appropriate box.

For any part number different from those listed above, please consult your local representative.







Dimensions are shown: mm Specifications and dimensions subject to change





KSM Series Side Actuated Detect Switches

KSM1131D LFG


KSM6161 LFG








KSM1131D LFG



KSM6161 LFG







First Angle Projection

Dimensions are shown: mm Specifications and dimensions subject to change

